

GUANTE - B271VRDCHA VIBRA-MCX

Synthetic leather palm, Spandex® back and Gelfoam® anti-vibration protection on palm and fingers.



NORMATIVE



Distributed by:



FEATURES

- Spandex® material at the back provides flexibility, breathability and a comfortable snug wearing.
- Gelfom® vibration reducing material on palm and fingers.
- Complies with EN ISO 10819 regarding vibration reducing gloves.
- Neoprene wrist with velcro closure.
- Knuckle padding for extra protection.
- Exclusive header card for retail.

MORE INFO

| Materials | Colour | Length | Sizes | Packaging |
|-------------------|--------|---|-------------------------------|------------------------------------|
| Synthetic leather | Black | M - 27 cm L - 28 cm XL - 29 cm XXL - 30 cm | 8/M 9/L 10/XL 11/XXL | 1 unit/package 50 unidades/caja |

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

| En388:2016 performance levels | 1 | 2 | 3 | 4 | 5 |
|-----------------------------------|-----|-----|------|------|----|
| 6.1 abrasion resistance (cycles) | 100 | 500 | 2000 | 8000 | - |
| 6.2 blade cut resistance (index) | 1,2 | 2,5 | 5 | 10 | 20 |
| 6.4 tear resistance (newtons) | 10 | 25 | 50 | 75 | - |
| 6.5 puncture resistance (newtons) | 20 | 60 | 100 | 150 | - |

| Eniso13997:1999 performance levels | A | B | C | D | E | F |
|------------------------------------|---|---|----|----|----|----|
| 6.3 tdm: cut resistance (newtons) | 2 | 5 | 10 | 15 | 22 | 30 |

Distributed by:

