

GUANTE GUANTES DE LÁTEX TOWA - 300 POWER GRAB

Seamless polyester/cotton glove with rough latex coating on palm



Distributed by:

NORMATIVE



FEATURES

- Ergonomic design perfectly fits to reduce hand fatigue.
- Textured latex coating promises outstanding tactility and grip performance.
- Extra coating of thumb area assures safety and protects from cuts and shocks (15% of hazards occur on this vulnerable area).
- Special long durability latex formula.
- Rubber proteins and chemical substances are leached to minimize allergic reactions. Assorted sizes.

USES

- Construction.
- DIY.
- Gardening.
- Glaziers.
- Assembly.
- Load and unload.
- General purpose.
- Shipping.

MORE INFO

Materials	Colour	Thickness	Length	Sizes	Packaging
Latex	Yellow / Blue	Gauge 10	XS - 23 cm S - 24 cm M - 25 cm L - 26 cm XL - 27 cm	6/XS 7/S 8/M 9/L 10/XL	12 pairs/package 72 pairs/box

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

Distributed by:

