


GUANTE GUANTES DE NITRILO TOWA - CJ569 ACTIVGRIP

Seamless Nylon® glove with double nitrile coating, water-proof and Microfinish®.



Distributed by:



NORMATIVE



FEATURES

- Its seamless Nylon® offers excellent comfort and flexibility, reducing hand fatigue.
- Microfinish® Nitrile coating providing comfort, flexibility and dexterity without scarifying toughness, providing great grip in dry, oily or wet surfaces.
- Fingers coated by the first layer for greater protection.
- Double full coating for extra water-tightness.

USES

- Building.
- Metal handling.
- Public service.
- Assembly and general purpose.
- Logistics and transport.

MORE INFO

Materials	Colour	Thickness	Length	Sizes	Packaging
Nitrile	Morado / Negro	Gauge 13	S - 24 cm M - 25 cm L - 26 cm XL - 27 cm	7/S 8/M 9/L 10/XL	12 pairs/package 144 pairs/box

NORMATIVAS


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection. If you want to know more about the main changes in these regulations, you can consult it through our website www.jubappe.es



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30

Distributed by:

