

**G002 - OILPROOF**  
Mechanical Protection Nitrile



EN 388:2016



4121X

EN 388:2016  
+A1:2018



4121X

DEXTERITY



EN ISO 14419:2010



"It is possible that gloves marked with previous standards are despatched. Cofra grants that all productions do not have technical and quality differences."

- Features**
- Oil Protection Technology - Double layer coating resistant to oils and greases
  - Double-layered nitrile palm: robust and water resistant
  - Superb grip on oily surfaces, thanks to their special sand finished nitrile coating
  - High abrasion resistance
  - Breathable nylon lining

**Coating** Sand finished nitrile, double-layer

**Lining** Nylon

**Gauge** 13

**Colour** Blue/black

**Application** Handling of metal parts, mechanical and car industry, building and construction, maintenance, setup, contact with oils and fats

<b>Sizes</b>	<b>K100A</b>	-	8 (M)	9 (L)	10 (XL)	11 (XXL)
	<b>KD00A</b>	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)

<b>Lenght</b>	23 cm	24 cm	25 cm	26 cm	27 cm
	9"	9,5"	9,9"	10,2"	10,6"



**SUPERB GRIP ON OILY SURFACES**



<b>Packaging</b>	Code		Quantity	
		G002-D100		1 dozen (12 single packed gloves)
	G002-DD00		1 dozen (1 bag containing 12 pairs)	
	G002-K100		Carton containing 6 dozen (72 single packed gloves)	
	G002-KD00		Carton containing 6 dozen (6 bags containing 12 pairs)	

**Distributed by:**



**Oil Protection Technology**

Double layer coating resistant to oils and greases. The internal layer resists to oil penetration and enhances durability. The sandblasted external layer resists to oils, providing a safe hold. The *Oil Protection Technology* line offers a range of various models, different from each other in terms of use and type of coating.



Mechanical Protection			Cut Protection	Cold Protection
Palm coating	¾ coating	Total coating	Total coating	¾ coating
				
<b>OILPROOF</b>	<b>SKINPROOF</b>	<b>TOTAL PROOF</b>	<b>BLACK DEEP</b>	<b>BUCKLER</b>
Breathability ●●●	Breathability ●●○	Breathability ●○○	Breathability ●○○	Breathability ●●○
Impermeability ●●●	Impermeability ●●●	Impermeability ●●●	Impermeability ●●●	Impermeability ●●●
Abrasion resistance ●●●	Abrasion resistance ●●●	Abrasion resistance ●●●	Abrasion resistance ●●●	Abrasion resistance ●●●

**Distributed by:**



**SAFETY TECHNICAL SPECIFICATIONS**

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	<b>7,15</b>
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	<b>NOT RECORDING</b>
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	<b>COMPLIANT</b>

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED
		1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	<b>4</b>
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	<b>1</b>
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	<b>2</b>
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	<b>1</b>
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>X</b>
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	<b>P</b>			<b>ABSENT</b>		<b>ABSENT</b>
		Achieved			Test not executed		

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved.

**Distributed by:**
