



**Prod. Ref.** PE320-000  
**Safety cat.** S1 PS SC FO SR  
**Range of sizes** 36 - 48 (3 - 13)  
**Weight (sz. 8)** 525 g  
**Shape** A  
**Width** 11

**Description:** Black innovative and breathable fabric shoe, **SANY-DRY®** lining, antistatic, anti-shock, slipping resistant, with non metallic **APT PLUS** midsole - type **PS** with Ø 3,0 mm nail.

**Plus:** **LIGHT FOAM** footbed, made of extremely soft and comfortable polyurethane foam. Punched, antistatic, its anatomical shape provides support to the plantar arch; covered with abrasion resistant fabric, it absorbs moisture and keeps always the foot dry; it guarantees excellent comfort and shock absorption. **LYCRA®** padded fort which hugs the foot, making it stable and enhancing comfort.

**Suggested uses:** Warehouses, transportation sector, industries

**Care and maintenance:** Clean after each use and dry off away from direct heat. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

**MATERIALS / ACCESSORIES**

**Complete shoe** **Toe cap:** **ALUMINIUM** made, ultra light, impact resistant until 200 J and compression resistant until 1500 kg

**Anti perforation midsole:** in multi-layers highly tensile fabric, penetration resistant, **Zero Perforation**

**Antistatic shoe:** the bottom is fit for the dissipation of electrostatic charges

**Energy absorption system**

**Upper** Innovative and breathable fabric, colour black

**Vamp** Textile, breathable, abrasion resistant, colour black

**lining** Thickness 1,2 mm

**Quarter** **SANY-DRY®**, breathable, abrasion resistant, colour black

**lining** thickness 1,2 mm

**Sole** Antistatic dual-density polyurethane directly injected in the upper:  
 Outsole: yellow, high density, slipping resistant, abrasion resistant and hydrocarbons resistant,  
 Midsole: black, low density, comfortable and anti-shock

Adherence coefficient of the sole (Slip resistance)

**Distributed by:**



**SAFETY TECHNICAL SPECIFICATIONS**

	Clause EN ISO 20345:2022	Description	Unit	Cofra result	Requirement
<b>Complete shoe</b>	5.3.2.6	Shock resistance (clearance after shock)	mm	<b>16</b>	≥ 14
	5.3.2.7	Compression resistance (clearance after compression)	mm	<b>18</b>	≥ 14
<b>Anti perforation midsole:</b>	6.2.1.1.4	Penetration resistance ( <b>PS</b> requirement with Ø 3,0 mm nail)	N	<b>1612</b>	≥ 1100
	6.2.2.2	Electric resistance	- wet	MΩ	<b>12,35</b>
- dry			MΩ	<b>77</b>	≤ 1000
<b>Upper</b>	6.2.4	Shock absorption	J	<b>30</b>	≥ 20
	5.4.6	Water vapour permeability Permeability coefficient	mg/cmq h	<b>&gt; 4,2</b>	≥ 0,8
mg/cmq			<b>&gt; 34,1</b>	≥ 15	
<b>Vamp</b>	5.5.4	Water vapour permeability Permeability coefficient	mg/cmq h	<b>&gt; 4,1</b>	≥ 2
			mg/cmq	<b>&gt; 47,2</b>	≥ 20
<b>Quarter</b>	5.5.4	Water vapour permeability Permeability coefficient	mg/cmq h	<b>&gt; 9,4</b>	≥ 2
			mg/cmq	<b>&gt; 76,4</b>	≥ 20
<b>Sole</b>	5.8.4	Abrasion resistance (lost volume)	mm <sup>3</sup>	<b>48</b>	≤ 150
	5.8.5	Flexing resistance (cut increase)	mm	<b>0</b>	≤ 4
	5.8.7	Interlayer bond strength	N/mm	<b>3,4</b>	≥ 3
	6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	<b>1,6</b>	≤ 12
	5.3.5.2	ceramic + detergent solution – forepart (contact angle 7°)		<b>0,41</b>	≥ 0,36
		ceramic + detergent solution – heel (contact angle 7°)		<b>0,35</b>	≥ 0,31
	6.2.10	SR : ceramic + glycerol – forepart (contact angle 7°)		<b>0,37</b>	≥ 0,22
		SR : ceramic + glycerol – heel (contact angle 7°)		<b>0,42</b>	≥ 0,19