



LIGHT PLUS P1

- Positioning belt
- Side "D" rings for positioning
- Adjustable and easy to fit
- Tool holder rings
- Not a fall arrest system
- NFC ready: Incorporates the new Iruclick NFC technology

Norm	EN358
Size	UNIVERSAL
Weight	580 g
Capacity	140 kg
Lifetime (years)	10 years of use +2 storage since fabric
Tape width	44mm

Materials

Tape	Polyester
Sewing thread	High Tenacity Polyamide
Metalic components	Steel
Finish	Deburring and polishing

Distributed by:





NEXION 150

Semi-static rope to make connections on them or use them as fastening elements.

As they do not include an energy absorber they cannot be used as a fall arrest system.

Distributed by:



Norm	EN 354
Length	1,5 m
Weight	186 g
Resistance	> 22 kN
Lifeline (years)	10
Diameter	12 mm

Materials

Rope	Polyamide
Thimble	PVC



SCREW-LOCK



STEELSAFE 981

Steel connector with manual threaded lock.

Distributed by:



Norm	EN 362
Weight	174 g
Opening	18 mm
Closure	Screw-Lock (manual thread)
Resistance	25 kN
Lifeline (years)	Unlimited

Material	
Body	Steel
Thread	Steel



LIGHTBAG

- Small 10 liter carrying bag for PPE's.
- It has cordino handles for shoulder transport.

Capacity	10 L
Shoulder pads for the back	Yes

Distributed by:

